

09/812,057

- 3 -

Amendments to the Claims


Please amend Claims 1, 22, 43, 44, 45, 46, 48, 49. The Claim Listing below will replace all prior versions of the claims in the application:

Claim Listing

1. (Currently amended) A method for classifying a communication signal, comprising:
- decomposing a subject signal into subbands;
  - determining a presence of energy in the subbands corresponding to at least one sinusoid in the subject signal; and
  - classifying the subject signal based on the presence of energy in the subbands to ~~instantiate~~ *as having a given communication protocol from among multiple communication protocols*; and
- enabling* ~~instantiating~~ a validation detector related to a protocol of the classified subject signal to validate the subject signal. *the given communication*
2. (Original) The method according to Claim 1, wherein decomposing the subject signal into subbands includes PS-IIR filtering.
3. (Original) The method according to Claim 1, further including engaging a preclassifier to estimate a frequency of a given sinusoid.
4. (Original) The method according to Claim 3, wherein estimating the frequency of the given sinusoid includes modeling the given sinusoid.
5. (Original) The method according to Claim 4, wherein modeling the sinusoid includes solving a second-order, auto-regression equation.

09/812,057

- 4 -

- 
6. (Original) The method according to Claim 3, wherein estimating the frequency of the given sinusoid includes accessing a look-up table having pre-determined ranges of data corresponding to the frequency of the given sinusoid.
  7. (Original) The method according to Claim 6, wherein the ranges of data are adjusted to account for estimation error due to finite signal length.
  8. (Original) The method according to Claim 3, further including windowing the subband prior to estimating the frequency of the given sinusoid.
  9. (Original) The method according to Claim 8, wherein windowing includes employing an N-point triangular window.
  10. (Original) The method according to Claim 1, wherein classifying results in classifying the signal as one of the following signal types: DTMF, MF-R1, ANS(V.25), LEC\_DIS, V.21, or AA.
  11. (Previously Presented) The method according to Claim 1, wherein determining a presence of energy in the subbands includes narrowing classification possibilities as a function of the presence, or absence, of energy in the subbands.
  12. (Original) The method according to Claim 11, further including notch filtering at select frequencies estimated to be sinusoid frequencies in the signal to further narrow classification possibilities.
  13. (Original) The method according to Claim 1, wherein decomposing the subject signal significantly reduces the bandwidth of the subbands compared to the subject signal.

09/812,057

- 5 -

14. (Original) The method according to Claim 1, further including processing the subject signal in predetermined frame sizes.
15. (Original) The method according to Claim 14, wherein the frame sizes are 10msec in length.
16. (Original) The method according to Claim 1, further including reporting the subject signal signal-type after three consecutive classifications identifying the same signal-type.
17. (Original) The method according to Claim 1, wherein classifying results in discriminating facsimile, modem, voice, and DTMF signals.
18. (Original) The method according to Claim 1, wherein executing the method uses an order of magnitude fewer processor instruction cycles than traditional methods for classifying communication signals.
19. (Original) The method according to Claim 1, wherein the method uses less than about 0.5 MIPS.
20. (Original) The method according to Claim 1, wherein plural such methods are operating on a single digital processor.
21. (Original) The method according to Claim 1, used in a media gateway.
22. (Currently amended) An apparatus for classifying a communication signal, comprising:  
a band-splitter decomposing a subject signal into subband signals;

09/812,057

- 6 -

an energy detector coupled to the band-splitter to determine a presence of energy in the subband signals corresponding to at least one sinusoid in the subject signal; and

a validation detector director coupled to said energy detector to classify the subject signal[[.]] based on the presence of energy in the subbands[[.]] to instantiate ; and

at least one validation detector, related to a protocol of the classified subject signal, instantiated by the validation detector director as a function of the classified subject signal, said at least one validation detector being coupled to the energy detector to validate the subject signal.

23. (Original) The apparatus according to Claim 22, wherein the band-splitter includes at least one PS-IIR filter.
24. (Original) The apparatus according to Claim 22, further including a preclassifier to estimate a frequency of a given sinusoid.
25. (Original) The apparatus according to Claim 24, wherein the preclassifier uses an automated modeling technique to determine the frequency of the given sinusoid.
26. (Original) The apparatus according to Claim 25, wherein the automated modeling technique solves a second-order, auto-regression equation.
27. (Original) The apparatus according to Claim 24, wherein the preclassifier accesses a look-up table having pre-determined ranges of data corresponding to the frequency of the given sinusoid.
28. (Original) The apparatus according to Claim 27, wherein the ranges of data are adjusted to account for estimation error due to finite signal length.

09/812,057

- 7 -

29. (Original) The apparatus according to Claim 24, wherein the preclassifier uses a window to filter the subband signal prior to estimating the frequency of the given sinusoid.
30. (Original) The apparatus according to Claim 29, wherein the window is an N-point triangular window.
31. (Original) The apparatus according to Claim 22, wherein the signal is classified as one of the following signal types: DTMF, MF-R1, ANS (V.25), LEC\_DIS, V.21, or AA.
32. (Previously Presented) The apparatus according to Claim 22, wherein the energy detector narrows classification possibilities as a function of the presence, or absence, of energy in the subband signals.
33. (Previously Presented) The apparatus according to Claim 32, wherein the validation detector director instantiates notch filters at select frequencies estimated to be sinusoid frequencies in the subject signal to further narrow classification possibilities.
34. (Original) The apparatus according to Claim 22, wherein the subband signals are significantly reduced in bandwidth compared to the subject signal.
35. (Original) The apparatus according to Claim 22, further including a frame-size control unit to control frame sizes of the signal being processed to be in predetermined frame sizes.
36. (Original) The apparatus according to Claim 35, wherein the frame sizes are 10msec in length.

09/812,057

- 8 -

37. (Original) The apparatus according to Claim 22, further including a reporting unit that reports the subject signal signal-type after three consecutive classifications identifying the same signal-type.
38. (Original) The apparatus according to Claim 22, discriminating facsimile, modem, voice, and DTMF signals.
39. (Original) The apparatus according to Claim 22, wherein executing the method uses an order of magnitude fewer processor instruction cycles than traditional methods for classifying communication signals.
40. (Original) The apparatus according to Claim 39, wherein classifying the signal uses less than about 0.5 MIPS.
41. (Previously Presented) The apparatus according to Claim 22, wherein said band-splitter, said energy detector, and said validation detector director are incorporated on a single digital processor.
42. (Original) The apparatus according to Claim 22, wherein the apparatus is used in a media gateway.
43. (Currently amended) An apparatus for classifying a communication signal, comprising:  
means for decomposing the signal into subbands;  
means for determining a presence of energy in the subbands corresponding to at least one sinusoid in the decomposed signal; and  
means for classifying the subject signal based on the presence of energy in the subbands ~~to-instantiate~~ ; and

09/812,057

- 9 -

means for instantiating a validation detector related to a protocol of the classified subject signal to validate the signal.

44. (Currently amended) A computer-readable medium having stored thereon sequences of instructions, the sequences of instructions including instructions, when executed by a digital processor, causes the processor to perform:
- decomposing a subject signal into subbands;
  - determining a presence of energy in the subbands corresponding to at least one sinusoid in the subject signal; ~~and~~
  - classifying the subject signal based on the presence of energy in the subbands ~~to instantiate~~ ; and
  - instantiating a validation detector related to a protocol of the classified subject signal to validate the subject signal.
45. (Currently amended) An apparatus, comprising:
- a receiver for receiving at least one analog signal having a protocol from among plural communication protocols;
  - an analog-to-digital converter to convert said at least one analog signal to a corresponding digital signal; and
  - a digital processor coupled to an output of the analog-to-digital converter to receive the digital signal, the digital signal processor executing program instructions to:
    - decompose the digital signal into subbands;
    - determine a presence of energy in the subbands corresponding to at least one sinusoid in the decomposed digital signal; ~~and~~
    - classify the received analog signal based on the presence of energy in the subbands ~~to instantiate~~ ; and
    - instantiating a validation detector related to a protocol of the classified analog signal to validate the analog signal.

09/812,057

- 10 -

46. (Currently amended) An apparatus, comprising:  
means for receiving at least one analog signal having a protocol from among plural communication protocols;  
means for converting said at least one analog signal to a corresponding digital signal; and  
means for processing the digital signal, including:  
means for decomposing the digital signal into subbands;  
means for determining a presence of energy in the subbands corresponding to at least one sinusoid in the decomposed digital signal; and  
means for classifying the received analog signal based on the presence of energy in the subbands ~~to instantiate~~ ; and  
means for instantiating a validation detector related to a protocol of the classified analog signal to validate the received analog signal.
47. (Original) The apparatus according to Claim 46, wherein the apparatus is a gateway coupled to a network.
48. (Currently amended) An apparatus, comprising:  
means for receiving at least one signal having a protocol from among plural communication protocols;  
means for decomposing the received signal into subbands; and  
means for classifying the received signal based on the signals in the subbands ~~to instantiate~~ ; and  
means for instantiating a validation detector related to a protocol of the classified received signal to validate the received signal.
49. (Currently amended) A central office, comprising:  
a first interface coupled to a first link to a digital network;  
a second interface coupled to a second link to at least one subscriber terminal in the digital network; and



09/812,057

- 11 -

a classifier coupled to said first and second interfaces, said classifier being employed to:

decompose a subject signal into subbands;

determine a presence of energy in the subbands corresponding to at least one sinusoid in the decomposed signal; and

classify the subject signal based on the presence of energy in the subbands ~~to~~ and

instantiate a validation detector related to a protocol of the classified subject signal to validate the subject signal.

50. (Previously Presented) A method for classifying a communication signal, comprising:

reducing an input signal into two lower-bandwidth signals;

detecting the presence of at least one sinusoid in the lower-bandwidth signals;

and based on the presence of said at least one sinusoid in the lower-bandwidth signals, instantiating a validation detector related to a protocol of the classified sinusoid to validate said at least one detected sinusoid is of a frequency corresponding to a frequency indicative of one of plural communication protocols.

51. (Original) The method according to Claim 50, wherein reducing the input signal into two lower-bandwidth signals includes:

sampling the communication signal with an A/D converter; and

filtering the sampled signal with at least one PS-IIR filter.

52. (Original) The method according to Claim 50, wherein detecting the presence of at least one sinusoid includes:

measuring energies in the lower-bandwidth signals; and

comparing the energies to expected energy levels.

09/812,057

- 12 -

- B
53. (Previously Presented) The method according to Claim 50, wherein validating said at least one detected sinusoid includes:
- filtering said at least one sinusoid with at least one corresponding filter;
  - and
  - for each filter, comparing the output of the filter to the input of the filter to test (i) the energy level and frequency of individual sinusoids, and, if applicable, (ii) the difference in magnitude of the energy levels of the two sinusoids composing the indications of a communication protocol employed by the communication signal.
54. (Original) The method according to Claim 50, further including determining the signal to be a facsimile, modem, voice, or DTMF signal.
-